



**Flat Hood, 60 cm, silbermetallic
5DA36453**

Design

- For installation in 60 cm wide wall unit
- Optionally exhaust air or recirculated air operation
- For recirculation operation, a standard recirculation set (optional accessory) is required

Design/Comfort

- Electronic control on the side
- 4-stage fan power (3 power stages and 1 intensive stage) adjustable via short-stroke keys with LED display
- Intensive stages with automatic reset
- Automatic three-stage fan run-on with digital display

Equipment

- Bright illumination with 2 x 1,5W LED module
- Color temperature: 3500 K
- Illuminance: 294 lux
- Cassette with aluminum frame
- Metal grease filter, dishwasher safe

Operating mode and power

- Fan capacity for exhaust air operation according to EN 61591: max. normal stage 271 m³/h, intensive stage 405 m³/h
- Noise values according to EN 60704-2-13 for exhaust air operation: Max. Normal stage: 62 dB(A) re 1 pW, Intensive stage: 69 dB(A) re 1 pW
- Noise min./max. normal stage: 49/62 dB
- Energy-saving operation due to efficient BLDC technology

Planning and installation information

- Unit dimensions (HxWxD): 203 x 598 x 290 mm
- Installation dimensions (HxWxD): 162 x 526 x 290 mm
- Exhaust air connection Ø 150 mm (Ø 120 mm enclosed)
- Length of connection cable: 1.75 m with plug
- without handle (available as optional accessory)

Environment and safety

- Energy efficiency class: A (on an energy efficiency class scale from A+++ to D)
- Average energy consumption: 22.2 kWh/year*
- Fan efficiency class: B*
- Lighting efficiency class: A*
- Grease filter efficiency class: C*
- Total connected load: 74 W

Special Accessories

- 5Z5145X5 : Standard air recirculation set
- 5Z5760N0 : Stainless steel handle bar

Equipment features:


- Approval certificates: CE, VDE
- Control: electronic
- diameter of the exhaust port: 120 / 150
- Material of grease filter: aluminum
- Odor filter: No
- Type of air duct: Convertible
- Delay shut off modes: 10
- Required accessories:
 - Type of lamps: LED
 - Type of grease filter: Cassette
 - Filter change reminder:
 - Plug type: Schuko/Gärdy.w. grounding
 - Housing material: galvanized
- Dimensions of the packed device: 12.20 x 25.19 x 14.17
- Net weight: 7.965 kg
- Gross weight: 9.400 kg
- Location of the blower: motor in the housing
- Back pressure flap: Yes

Consumption and connection values:


- Connected load: 74 W
- Fuse protection: 10 A
- Voltage: 220-240 volt
- Frequency: 50; 60 Hz

EAN-Nr.:4251003106268


14-12-2021




Maße in mm




Tiefenanpassung des Filterauszuges bis 29 mm möglich
Maße in mm




Maße in mm




Maße in mm



Maße in mm



Maße in mm



Maße in mm