



EAN: 4251003106954

T-Shape hood 90 cm
5DB69753
Stainless Steel

Output, consumption

Energie-Effizienzklasse: C

- Average energy consumption: 64,8 kWh / year *
- Fan efficiency class: E
- Lighting efficiency class: D
- Grease filter efficiency class: C
- Total connected load: 123W
- Voltage: 220 - 240V
- noise min./max. Normal level: 67 dBA in Max
- fan power max. Normal Level:
 - with exhaust air operation max(m3/h): 430
 - with recirculation mode max.(m3/h): 265

Equipment / comfort

- Fan power 3-level controlled by pushbuttons
- Even, bright lighting with 2 x 4W LED lamps
- Illuminance: 100 lux
- Color temperature: 3000 K
- Metal grease filter, dishwasher safe
- Follow-up function: n0
- Filter change reminder: no

Technical data and dimensions (HxBxT)

- Exhaust air: 66,7-94,0x89,8x45,0
- Recirculation air 79,0-106x89,8x45,0
- Appliance dimensions (packed): 603 x 972 x 415 mm
- Net weight (kg): 14
- Gross weight (kg): 19

Accessories:

Optional accessories:

| | | |
|------------------------------|-----------|---------|
| Charcoal filter | 5Z 9114X1 | EG18611 |
| Regenerative Charcoal filter | 5Z9114X2 | EG18081 |
| Shaft lengthening 990 mm | 5Z9119X1 | EG18612 |

Available color options:



Ausstattungsmerkmale:

- Device type: T-Shape hood
- Color of the fireplace: stainless steel
- Type: wall
- Approval certificates: CE/UKCA
- Length of connection cable (cm): min 120
- Control: push buttons
- Regulation of power levels: 3
- Diameter of exhaust air outlet (mm): 150
- Material of grease filter: Aluminum
- Type of air flow: upwards

Consumption and connection values:

- Connected load (W): 123
- Voltage (V): 220-240
- Frequency (Hz): 50
- Connector type: EU
- Type of installation: wall
- Housing material: housing made of stainless steel
- Approval certificates: CE/UCKA
- Required distance between tray / cooker:
 - Electric: 500mm, Gas: 650mm
- Position of the blower: motor in the housing