



SIX60260
Glass ceramic black
Downdraft 60cm

Power / Consumption

- Energy efficiency class: A
- Average energy consumption: 45.3 kW/a
- Fan efficiency class: A
- Lighting efficiency class: -
- Grease filter efficiency class: C
- Total connected load: 165 W
- voltage: 220/240V
- Sound power dB(A): 74

Equipment / Comfort

- Suitable for mounting in kitchen line or island
- Choice of exhaust air or recirculated air operation
- Fan capacity 6-stage adjustable by TouchControl
- 7-segment LED display
- For exhaust air 5 power levels + 1 intensive level
- With recirculated air 6 power levels
- 1 intensive stage with automatic reset on exhaust air
- Automatic fan run-on
- Filter change reminder: Yes
- Metal grease filter and carbon filter saturation indicator (LED)
- Automatic overrun with recirculated air
- Water collector: 1 liter capacity
- Powerful and quiet blower
- performance according to EN 61591:
 - exhaust air operation (m³/h): 422
 - intensive stage exhaust air operation (m³/h): 565
 - recirculating air operation (m³/h): 320
 - intensive stage air recirculation mode (m³/h): 425

Technical data and dimensions (HxWxD)

- Device dimensions: 59 x 600 x 520 mm (radius 5)
- Installation dimensions: 0-59 x 561 x 484 mm (radius 5)
- Device dimensions (packed): 1040 x 740 x 505 mm
- Net weight (kg): 21.2
- Gross weight (kg): 32

Accessories

- Metal grease filter, dishwasher safe

Special accessories:

- 5Z6005KF1 - Charcoal filter
- 5Z9104X1 - Air outlet kit right
- SLG5IX90 - Plinth ventilation grille

Available colour variations:

Equipment features:

- Device type: Induction with integrated extractor fan
- Design: Induction with integrated extractor hood
- Connection cable length (cm): 150
- Approval certificates: CE

Consumption and connection values:

- Connected load (W): 165
- Voltage (V): 220/240
- Frequency (Hz): 50/60
- Plug type: Schuko

EAN-Nr. 4251003105087

