



<p>5IX92291 Glass ceramic black Downdraft 90cm</p> <p>Power / Consumption</p> <ul style="list-style-type: none"> • Energy efficiency class: A++ • Average energy consumption: 37.2 kW/a • Fan efficiency class: A • Lighting efficiency class: - • Grease filter efficiency class: B • Total connected load: 160 W • Voltage: 220/240V • Sound power dB(A): min 47 max 65 Int. <p>Equipment / Comfort</p> <ul style="list-style-type: none"> • Suitable for mounting in kitchen line or island • Choice of exhaust air or recirculation mode • Electronic opening of the extractor hood • Fan capacity 6-stage adjustable by TouchControl • 7-segment LED display • For exhaust air 5 power levels + 1 intensive level • With recirculated air 6 power levels • Intensive levels (automatic) reset • Three-stage fan run-on (5 / 10 / 20 min) (LED) • Filter change reminder: Yes • Metal grease filter/carbon filter saturation indicator (LED) • Cleaning of metal grease filter: after 40 operating hours • Automatic overrun with recirculated air • Water collector: 0.75 litre capacity • Powerful and quiet blower • performance according to EN 61591: <ul style="list-style-type: none"> - Fan power - exhaust air operation (m³/h): 570 - Fan power intensive exhaust air mode (m³/h): 660 - Fan power-circulating air operation (m³/h): 450 - Fan power intensive circulating air mode (m³/h): 500 <p>Technical data and dimensions (HxWxD)</p> <ul style="list-style-type: none"> • Unit dimensions: (h/w/d) 0-5 x 900 x 530 mm • Installation dimensions: (h/w/d) 50-55 x 860 x 490 mm • Device dimensions (packed): 1040 x 740 x 505 • Net weight (kg): 24,71 • Gross weight (kg): 36,2

<p>Accessories</p> <ul style="list-style-type: none"> • Metal grease filter, dishwasher safe 						
<p>Special accessories:</p> <table border="0"> <tr> <td>2-Set Charcoal Filter</td> <td>5Z9009LF1</td> </tr> <tr> <td>Air outlet kit right</td> <td>5Z9104X1</td> </tr> <tr> <td>Plinth ventilation grille</td> <td>SLGSIX90</td> </tr> </table>	2-Set Charcoal Filter	5Z9009LF1	Air outlet kit right	5Z9104X1	Plinth ventilation grille	SLGSIX90
2-Set Charcoal Filter	5Z9009LF1					
Air outlet kit right	5Z9104X1					
Plinth ventilation grille	SLGSIX90					
<p>Available colour variations:</p>						

<p>Equipment features:</p> <ul style="list-style-type: none"> • Device type: Induction with integrated extractor fan • Design: Induction with integrated extractor hood • Connection cable length (cm): 150 • Approval certificates: CE
<p>Consumption and connection values:</p> <ul style="list-style-type: none"> • Connected load (W): 165 • Voltage (V): 220/240 • Frequency (Hz): 50/60 • Plug type: Schuko

EAN-Nr. 4251003105063

