



**51X99291
Glass ceramic black
Downdraft 90cm**

Power / Consumption

- Voltage: 220 - 240 V
- Total connected load 7.4 kW
- 4 induction cooking zones with booster:
- 4 cooking zones Ø 22 cm, 2.1 kW (3.7 kW)

Equipment / Comfort

- Frameless
- Touch Control with Slider Function with LED White
- Boost function for all induction cooking zones
- Electronic control in 10 power levels
- Main switch for hob and extractor fan
- Toggle function with fixed temperatures: (40 °C, 70 °C and 98 °C)
- Cooking chef Mode,
- Pause and recall
- Residual heat display
- Pot detection
- Parental control
- Timer
- Countdown function
- 2 x bridge function
- Flush mountable
- No direct left-sided planning of dishwashers, underframe coolers, plinth drawers with recirculation variant
- Min. cabinet width 800 mm
- Worktop depth min. 600 mm (with planning of niche cladding correspondingly deeper)
- Plinth height min. 100 mm

Technical data and dimensions (HxWxD)

- Device dimensions: 58 x 900 x 530 mm
- Installation dimensions: 58 x 862 x 495 mm
- Device dimensions (packed): 1040 x 740 x 505 mm
- Net weight (kg): 30,8
- Gross weight (kg): 39,65

Special Accessories

- 5Z9105X1 Charcoal filter
- 5Z9104X1 Air outlet kit right
- SLG51X90 plinth ventilation grille

Equipment features:

- Type of appliance: Cooking unit glass ceramic
- Design: Built-in device
- Energy source: electric
- Position of the control unit: Front
- LED display white
- Approval certificates: CE
- Length of connection cable (cm): 150

Available colour variations:

Consumption and connection values:

- Total connected load (W): 7400
- Protection (A): -
- Voltage (V): 220-240
- Frequency (Hz): 50; 60
- Approval certificates: CE
- Connector type: without connector
- Minimum distance from counter front (mm): 50
- Minimum distance from rear wall (mm): 42

Accessories:

EAN-Nr.: 4251003105056

